

ALBANY FIRE PROTECTION, INC.

Hydrant Flow Test Report

Test Date 6/21/2019

Test Time 10:48

Location

Route 9 W &
Riverview Drive

Tested by

Robert Hotaling
Albany Fire Protection, Inc.
1853 Avenue B
Watervliet, NY 12189

Notes


Read Hydrant

100 psi static pressure
62 psi residual pressure
160 ft. hydrant elevation

Flow Hydrant(s)

Outlet	Elev	Size	C	Pitot Pressure	Flow
#1	190	2.5	.9	54	1233 gpm

Flow Graph




1853 AVENUE B / WATERVLIET NY 12189

Large LED Wallpack – Zero Uplight

Largest in the Litepak product family, the LNC4 is designed for perimeter illumination for safety, security and identity. Replaces up to 400w HID luminaires one-for-one replacement covering existing installation footprint. No uplight and lower glare lenses offer neighbor friendly lighting at typical mounting heights of 15-25'. Units have protective polyester powder coat finish for long lasting appearance. Ideal for schools, factories, hospitals, warehouses and retail applications. Energy efficient LEDs provide 70%+ energy savings with little to no maintenance when compared to traditional light sources.

Die-cast aluminum housing protects components and provides an architectural appearance. Casting thermally conducts LED heat to optimize performance and long life.

- 120-277, 347 and 480 voltage, 50/60Hz, 0-10V dimming driver
- Electronic driver
- Surge protection – 10KA
- 3000K, 4000K and 5000K CCT nominal with 70 CRI
- 36 and 44 LED configurations available
- Zero uplight distributions using individual acrylic LED optics provide IES type II, III and IV distributions
- Features long-life with L96 of 25,000 hours (Projected per IESNA TM-21-11)
- Optional frosted acrylic diffuser for reduced glare or inverted up mounting
- DesignLights Consortium® (DLC) qualified. Please refer to the DLC website for specific product qualifications at www.designlights.org



c us Optional Motion Sensor



*3000K and warmer CCTs only

STOCK ORDERING INFORMATION

Catalog Number	Description	Distribution	Wattage	Lumens	LPW	Voltage	# of Drivers @ Drive Current	Wgt lbs. (Kg)	PKG. CODE
LNC4-36L-4K	36 LED Configuration, 4000K, Dark Bronze	Type IV	124.6	10,754	86.3	120-277	2 @ 1050mA	27.0 (12.2)	FCC
LNC4-44L-4K	44 LED Configuration, 4000K, Dark Bronze		152.6	13,477	88.3			27.0 (12.2)	FCC
LNC4-44L-5K	44 LED Configuration, 5000K, Dark Bronze		152.1	13,342	87.7			27.0 (12.2)	FCC
LNC4-44L-4K-7PR	44 LED Configuration, 4000K, Dark Bronze, 7 Pin		152.6	13,477	88.3			27.0 (12.2)	FCC
LNC4-44L-4K-SCP	44 LED Config., 4000K, Dark Bronze, Occ. Sensor		152.6	13,477	88.3			27.0 (12.2)	FCC

MADE-TO-ORDER ORDERING INFORMATION - CONFIGURABLE (SEE SPEC SHEET FOR PERFORMANCE INFORMATION AND DETAILS)

LNC4	-	36L	-	4K	-		-		-		-	
FAMILY	NUMBER OF LEDS	CCT	DRIVE CURRENT	IES DISTRIBUTION	VOLTAGE	FINISH	CONTROL OPTIONS	OPTIONS				
LNC4 Large Litepak Wallpack	36L 36LED	3K 3000K	035 350mA	2 Type II	U 120V-277V	DB Bronze	PCU Universal Button PC	F ¹	Fusing! (must specify voltage per footnote)			
	44L 44LED	4K 4000K	065 650mA	3 Type III	1 120V ¹	BL Black	7PR ⁵ NEMA 7-Pin twistlock receptacle	CS	Frosted acrylic diffuser			
		5K 5000K	1050 1050mA	4 Type IV	2 208V ¹	WH White	SCP ^{3,4} Programmable occupancy sensor	CSU ²	Frosted acrylic diffuser required for inverted fixture installations (Factory install only)			
					3 240V ¹	GR Gray	SWP ^{1,7} SiteSync wireless pre-commissioned	E ^{1,6}	Integral battery backup rated for 0°C.			
					4 277V ¹	PS Platinum	RD Red	EH ^{1,6}	Integral battery backup with heater rated for -30°C.			
					5 480V ¹	FG Forest Green	CC Custom Color					
					F 347V ¹	RD Red	SWPM ^{1,4,7,8} SiteSync wireless pre-commissioned w/ occupancy sensor					

¹ Must specify voltage (battery backup 120 or 277V only, SiteSync 120, 277 or 347V only)

² Factory install only. Not available with SCP or SWPM sensor/control options

³ Must order minimum of one remote control to program dimming settings, 0-10V fully adjustable dimming with automatic daylight calibration and different time delay settings, 120-277V only.

⁴ PC option not applicable, included in sensor. Must specify sensor height (8F = up to 8ft, 20F = up to 20ft)

⁵ Accepts standard 3, 5, and 7-Pin ANSI controls (by others). Not available with PCU, SWP or SWPM control options

⁶ 36L-650mA version only. Not available with SWP or SWPM control options.

⁷ Must specify group and zone information at time of order. See www.hubbellighting.com/products/sitesync for further details.

⁸ Specify time delay, dimming level and mounting height

CATALOG NUMBER	DESCRIPTION
LNC4-CS	Frosted acrylic diffuser reduces surface brightness and glare with a roughly 20% lumen reduction
SCP-REMOTE2*	Remote control for SCP option. Order at least one per project to program and control
SWUSB**	SiteSync interface software loaded on USB flash drive for use with owner supplied PC (Windows based only). Includes SiteSync license, software and USB radio bridge node.
SWTAB**	Windows tablet and SiteSync interface software. Includes tablet with preloaded software, SiteSync license and USB radio bridge node.
SWBRG*	SiteSync USB radio bridge node only. Order if a replacement is required or if an extra bridge node is requested.

* Must order minimum of one remote control to program dimming settings, 0-10V fully adjustable dimming with automatic daylight calibration and different time delay settings, 120V or 277V only

** When ordering SiteSync at least one of these two interface options must be ordered per project.

+ If needed, an additional Bridge Node can be ordered.


DIMENSIONS

A	B	C	D	E	Weight
17.2"	10.5"	9.9"	6.5"	8.9"	27 lbs.
436 mm	266 mm	251 mm	165 mm	226 mm	12.3 kg


SPEC SCP/SCO & SWPM MOUNT HEIGHT

-8F Up to 8ft mount height



-20F Up to 20ft mount height



WITHOUT DIFFUSER



WITH DIFFUSER



HUBBELL
Outdoor Lighting