

**BUILDING CODE & GENERAL NOTES FOR PROJECT:**

1. ...
2. THE ARCHITECT IS NOT BEING HIRED FOR PERIODIC FIELD INSPECTIONS OF THE CONSTRUCTION. THE ARCHITECT IS TO BE INFORMED OF ANY UNKNOWN CONDITIONS THAT HAVE BEEN DISCOVERED AND THAT MAY CONSTITUTE DISCREPANCIES BETWEEN THE PLANS & SPECIFICATIONS WITH THE EXISTING CONDITIONS.
3. CONTRACTOR SHALL PERFORM ALL WORK REQUIRED FOR THE COMPLETION OF THE PROJECT, WHETHER OR NOT ALL ASPECTS ARE INDICATED ON THE PLANS.
4. ALL WALLS AND FLOORS ARE TO BE ADEQUATELY BRACED & SHORED UNTIL ALL PERMANENT FRAMING SUPPORTS ARE IN PLACE.
5. THE CONTRACTOR SHALL NOT CUT ANY STRUCTURAL MEMBERS WITHOUT THE ARCHITECT'S CONSENT AND AS APPROVED BY THE BUILDING CODE.
6. TESTING LABORATORY SERVICES MAY BE REQUESTED BY THE ARCHITECT AND MAY INCLUDE BUT NOT LIMITED TO: SOIL AND MATERIAL COMPACTION, AND MATERIALS TESTING.
7. ALL WORK MUST COMPLY WITH THE INTERNATIONAL RESIDENTIAL CODE OF 2015 AND NYS UNIFORM SUPPLEMENT CODE OF 2016.
8. ALL WORK MUST COMPLY WITH THE INTERNATIONAL ENERGY CONSERVATION CODE OF 2015 AND THE SUPPLEMENT TO THE NYS ENERGY CONSTRUCTION CODE OF 2016.
9. ALL ELECTRICAL WORK MUST COMPLY WITH THE 2015 INTERNATIONAL ELECTRICAL CODE AND INTERNATIONAL RESIDENTIAL CODE, AND ALL APPLICABLE CODES AND REGULATIONS. WORK MUST BE INSPECTED AND APPROVED BY A LICENSED UNDERWRITER. INSPECTION STICKERS MUST BE MOUNTED TO THE ELECTRICAL PANEL BOX.
10. ALL PLUMBING AND MECHANICAL WORK MUST COMPLY WITH THE 2015 INTERNATIONAL RESIDENTIAL CODE, 2015 INTERNATIONAL MECHANICAL CODE AND ALL APPLICABLE CODES AND REGULATIONS.

**INTERNATIONAL ENERGY CONSERVATION CODE - 2015**

NOTE: NYS 2016 SUPPLEMENT HAS NO ADDITIONAL ENERGY REQUIREMENTS FOR SINGLE FAMILY HOMES.

REQUIRED

PROVIDED

GLAZING U FACTOR - 0.32  
CEILING R VALUE - R-49  
EXTERIOR WALL R VALUE - R-20  
FLOOR R VALUE - R-30  
BASEMENT WALL R VALUE - R-19  
...  
PREScriptive COMPLIANCE  
...  
CHAPTER 4 OF THE 2015 ENERGY CODE OF NYS - TABLE 402.1.2 -  
RESIDENTIAL COMPLIANCE DID NOT WORK  
INSULATION MUST MEET DOOR BLOWER TEST AND AIR LEAKAGE TEST PER THE CODE REQUIREMENTS FOR EACH  
SEAL AND CAULK ALL JOINTS AND PENETRATIONS.  
DUCT WORK IN UNCONDITIONED SPACE MUST BE SEALED AND TESTED FOR LEAKAGE PER THE CODE.

ENERGY EFFICIENCY NOTES -

1. NI 102.4 (R402.40) AIR LEAKAGE FOR BUILDING THERMAL MASS - TESTING WILL INCLUDE A DOOR BLOWER TEST AS PER CODE - 3ACH50/VOLUME TO BE MET.

2. NI 102.4.1.2 FOR AIR LEAKAGE RATES.

3. SEAL AND CAULK ALL JOINTS AND PENETRATIONS FOR AIR LEAKAGE PREVENTION.



4. NI 103 (R403) SYSTEMS TESTING

5. NI 103.3.2 (R403.3.2) - SEALING OF DUCTWORK.

6. NI 103.3.3 AND NI 103.3.4 (R403.3.3) DUCT TESTING LEAKAGE REQUIREMENTS - 4% VALUE TO BE MET.

ENERGY NOTES :

1. A MINIMUM OF 75% OF THE LAMPS IN PERMANENTLY INSTALLED LIGHTING FIXTURES SHALL BE HIGH EFFICIENCY LAMPS PER SECTION 103.9 OF THE 2015 RESIDENTIAL CODE.
2. RECESSED LUMINARIES INSTALLED IN BUILDING THERMAL ENVELOPE SHALL BE SEALED WITH A GASKET OR CAULK BETWEEN THE HOUSING AND THE INTERIOR WALL OR CEILING TO LIMIT AIR LEAKAGE BETWEEN CONDITIONED AND UNCONDITIONED SPACES PER SECTION 102.4.5 OF THE 2015 RESIDENTIAL CODE.
3. CONTRACTOR SHALL PROVIDE PROGRAMMABLE THERMOSTATS TO CONTROL THE HVAC SYSTEMS PER 103.12 OF THE 2015 RESIDENTIAL CODE.
4. ALL DUCTS, AIR HANDLERS, FILTER BOXES AND BUILDING CAVITIES USED AS DUCTS SHALL BE SEALED. JOINTS AND SEAMS SHALL COMPLY WITH MI 60.3 OF THE 2015 RESIDENTIAL CODE. BUILDING FRAMING CAVITIES SHALL NOT BE USED AS SUPPLY DUCTS.
5. ALL MECHANICAL SYSTEMS HAVING CAPABLE OF CARRYING FLUIDS ABOVE 105 DEGREES F OR BELOW 55° F SHALL BE INSULATED TO A MINIMUM OF R-3.
6. ATTIC ACCESS SHALL BE INSULATED WITH THE SAME R-VALUE AS THE ATTIC. WEATHERSTRIPPED AND LATCHED AS PER SECTION 10102.2.3
7. 2015 RESIDENTIAL BUILDING CODE.
8. AIR TIGHTNESS AND INSULATION SHALL BE VERIFIED BY VISUAL INSPECTION PER 110.4.4.3.2 OF THE 2010 RESIDENTIAL BUILDING CODE.
9. ALL GAS PIPING TO BE GROUNDED TO A BUILDING GROUNDING ELECTRODE.
10. ALL ELECTRICAL OUTLETS MUST BE ARC FAULT PROTECTED.



**WINDOW NOTES:**

1. BASIS OF DESIGN FOR WINDOWS ARE SILVERLINE BY ANDERSEN 3000 SERIES.
2. CONFIRM ROUGH OPENING DIMENSIONS WITH MANUFACTURER. DIMENSIONS PROVIDED ARE UNIT DIMENSIONS.
3. SEE EGRESS OPENING DIMENSIONS WITH MANUFACTURER. DIMENSIONS PROVIDED ARE UNIT DIMENSIONS.
4. WINDOW SILLS SHALL BE A MINIMUM OF 24" ABOVE FINISHED FLOOR. SEE NOTE #6 B BELOW.
5. WINDOWS ARE SILVERLINE BRAND BY ANDERSEN WINDOWS. 3000 SERIES. DOUBLE HUNG, LOW-E, INSULATED, DOUBLE GLAZED. TILT WASH. VINYL FRAME WITH GRILLE PANES - GLAZING U FACTOR: 0.32 SIZES NOTED BELOW ARE NOMINAL.
6. WINDOWS ON THE FLOOR PLANS OR ELEVATIONS WITH AN 'A' DESIGNATION OR HAVE A SILL HEIGHT LESS THAN 24 INCHES A.F.F. AND GREATER THAN 72 INCHES ABOVE THE FINISHED GRADE OR OTHER SURFACE HAVE FALL PROTECTION PER SECTION R3.12. TYP. PROTECTION CAN INCLUDE:
  1. OPERABLE WINDOWS SHALL NOT ALLOW A 4 INCH SPHERE TO PASS THROUGH.
  2. OPERABLE WINDOWS SHALL HAVE FALL PROTECTION COMPLYING WITH ASTM F2090.
  3. OPERABLE WINDOWS SHALL HAVE CONTROL DEVICES THAT COMPLY WITH ASTM F2090 AND NOT REDUCE THE CLEAR OPENING WIDTH SPECIFIED.


NOTES:

1. VERIFY NEW WINDOWS COMPLY WITH WINDOW NOTES ON PLAN A2 FOR FALL PROTECTION - SILL HEIGHT AND GRADE OR OTHER EXTERIOR SURFACE HEIGHTS, TYP.
2. SEE BEARING NOTE THIS PAGE, TYP.

**BEARING NOTE:**

1. VERIFY SECOND FLOOR POSTS AND HEADERS CONTINUE TO BEARING THROUGH FIRST FLOOR FRAMING, TYP.

2. SEE BEARING NOTE THIS PAGE, TYP.






WINDOW & PATIO DOOR SCHEDULE					
NO.	UNIT WIDTH	UNIT HEIGHT	MATERIAL	CLEAR OPENING SF	VISBLE SF
1	3'-0"	4'-6"	VINYL	6.75	12.79
2	(2) 3'-0"	4'-6"	VINYL	13.5	25.58
3	3'-0"	3'-0"	VINYL	5.33	10.16
3T	3'-0"	3'-0"	VINYL	5.33	10.16
4	2'-0"	3'-2"	VINYL	5.06	5.87
5	2'-0"	4'-6"	VINYL	2.3046	2.3046
6	5'-0"	4'-0"	VINYL	17.6	20.46
7	6'-0"	6'-6"	PATIO DOORS	17.6	20.46
9	3'-2"	3'-0"	VINYL	5.33	10.16
10	3'-0"	4'-2"	VINYL	6.00	12.00

REVISION					
OWNER REVIEW	OWNER REVIEW	BD SUBMISSION	BD SUBMISSION	FIRST FLOOR CONST.	NEW
BD SUBMISSION	BD SUBMISSION			WINDOWS, FOAM INSULATION	
4-16-18	4-16-18	4-5-1-18	4-5-1-18	5-6-6-18	6-6-6-18
1	2				

DAVID NIEMOTKO ARCHITECTS, P.C.  
167 STAGE ROAD  
MONROE, NEW YORK  
(845) 774-7523 PH. & FAX (845) 401-2891 MOBILE  
WWW.NIEMOTKOARCHITECTS.COM

NOTE: FOR AUTHENTICITY  
SEAL MUST BE  
SIGNATURE MUST  
BE IN COLOR  
BOTH CANNOT  
BE COPIED



NOTE: IF EARTH IS DISTURBED AND/OR THE OVER EXCAVATION AREAS WITHIN THE GARAGE, INSTALL STRUCTURAL FILL AND TAMP IN 8 INCH LUMPS TO 95% COMPACTION, TYP.

1. CONCRETE FOUNDATION WALLS, PIERS, AND FOOTINGS SHALL BE 3,000 PSI, 28 DAY COMPRESSIVE STRENGTH MIN.

2. WINTER CONCRETE DESIGN MIX SHALL HAVE 4,000 PSI, 28 DAY COMPRESSIVE STRENGTH.

3. SOIL CLASSIFICATION IS ASSUMED TO BE GRADE 1, GM AND SM TYPE - 2000 PSI. OWNER TO VERIFY.

4. FOUNDATION CONFORMS TO TABLE R404.1 (1-14) MAX UNBALANCED BACKLASH HEIGHT OF 7 FEET.

5. EXTERIOR CONCRETE SHALL HAVE AN EXTERIOR APPLICATION DESIGN MIX WITH THE APPROPRIATE AIR CONTENT AND SLUMP.

6. VIBRATE ALL FOUNDATION WALL OPENINGS WITH 2#45 ALL AROUND AND EXTEND BEYOND OPENING 2-0 ALL AROUND MIN.

7. PROVIDE ADDITIONAL 4-#4 VERTICAL FULL HEIGHT AND TIED TOGETHER AT EACH BEAM POCKET.

8. POCKETS FOR BEAMS SHALL HAVE 1/2" CLEARANCE ALL AROUND FLASH AREAS OF BEAM IN POCKET AND SHIM BEAM AS NEEDED WITH METAL.

9. STEEL FOOTINGS SHALL CONFORM WITH DETAILS 20244 REINFORCING EACH WAY, TYP.

10. ALL DAILY COLUMNING SHALL BE INSTALLED PER CODE WITH TOP AND BOTTOM PLATES AND LVL TO CONNECTORS

4 A2 SCALE: NTS FIGURE RCD2.6(2)

4 A2 SCALE: NTS FIGURE RCD2.6(2)